

Blasting Measurement Microphone

FOR USE WITH ECHOPRO & FUSION BLAST MONITOR

APPLICATIONS

The 7052S/4052 Measurement Microphone/Preamp is intended for OEM applications requiring a cost-effective, stable, flat, and rugged mic. The back electret construction eliminates the need for any polarizing voltage. The Titanium diaphragm assures both short and longterm stable frequency and amplitude response over a wide range of environmental conditions. The performance exceeds IEC specifications for TYPE 2 microphones. The ES7052/ES4052 extends the low frequency performance of the standard 7052/4052 mic/preamp combination.



Perfect for Compliance
Monitoring and other air pressure
monitoring applications.

*Microphone and pre-amp assembly shown
at right with optional 3" foam wind shield.*



TECHNICAL SPECIFICATIONS

7052/ 4052

Frequency Response:	20 Hz to 20 kHz +/- 3dB Determined by the preamp
Sensitivity:	7052S Capsule - (-)33dBV/Pa (20 mV) Open Circuit
Preamp Loss:	-Preamp Loss: -2 dB Typ
Preamp Operating Voltage:	(+)9Vdc to 15 Vdc
Usable Dynamic Range:	24 dBA (equivalent "A" weighted noise floor) Upper Limit (Determined by Preamp Operating Voltage) 9Vdc - 130 dBSPL 15 Vdc - 140 dBSPL
Preamp Connector	Cable - ACO Pacific Model Number 7052SC
Connector Pinout:	Pin A - (V+) Pin B - N/C Pin C - Signal Pin D - N/C Pin E,F -(V-) Shield at Equipment En

ES7052H / ES4052

Frequency Response:	<1 Hz to >100 Hz +1/- 2dB with ES4052 Preamp
Sensitivity:	7052H Capsule -22dBV/Pa (22mV/Pa) Open Circuit typ On ES4052 Preamp (23 dB loss) -45 dBV/Pa (2 mV/Pa) typ. preamp out
Preamp Loss:	-18 dB Typ –measured with DM2-22 (22pF) Dummy Mic 12Vdc power About -20 dB loss with ES7052H capsule capacitance Capsule "H" Grid Holes in place of slotted Testing to 1 Hz 1Hz (-)2 dB relative to100 Hz response as measured with a B&K 4221 LF source
Preamp Operating Voltage:	(+) 9Vdc to 15 Vdc
Usable Dynamic Range:	Upper Limit (Determined by Preamp Operating Voltage) 12 Vdc – 150+ dBSPL microphone dependent (2 Vrms)
Preamp Connector:	Cable - 7052SC supplied standard or 7052FC (flange) an option
Connector Pinout:	Pin A - (V+) Pin B - N/C Pin C - Signal Pin D - N/C Pin E,F -(V-) Shield at Equipment End

MODIFICATIONS / ES7052	Capsule "H" Grid Holes in place of slotted Testing to 1 Hz 1Hz (-)2 dB relative to100 Hz response as measured with a B&K 4221 LF source
MODIFICATIONS / ES4052	Z in resistor 5000 Megohms Shunt capacitor 150pF (acts as attenuator)

